

Loose-Lay Collection
Vinyl Flooring

asset
space becomes place



Technical Data LOOSE-LAY COLLECTION

	LOOSE-LAY/55	LOOSE-LAY/30
Covering type in accordance with EN 649	Heterogeneous Plankwood/Tiles	Heterogeneous Plankwood/Tiles
Number of colours	14 Planken / 6 Fliesen	14 Planken / 6 Fliesen
Pack. Unit/Pallet	914x183 mm: 1.67 m ² /125.25 m ² 457x457 mm: 1.67 m ² /120.24 m ² 610x305 mm: 1.67 m ² /120.24 m ² 600x600 mm: 1.80 m ² /129.60 m ²	914x183 mm: 1.67 m ² /125.25 m ² 457x457 mm: 1.67 m ² /120.24 m ² 610x305 mm: 1.67 m ² /120.24 m ² 600x600 mm: 1.80 m ² /129.60 m ²
Performance classification EN 685	23, 33, 42	21-23, 31
Total thickness EN 428	4.2 mm	4.2 mm
Wear layer thickness EN 429	0.55 mm	0.3 mm
Surface treatment	yes/PU	yes/PU
Bevelled edges	Yes	No
Total weight EN 430	7.00 kg/m ²	7.23 kg/m ²
Residual indentation EN 433	0.06 mm	0.06 mm
Castor chair suitability EN 425	suitable for castor chairs in acc. with EN 12529, type W	suitable for castor chairs in acc. with EN 12529, type W
Underfloor heating	suitable (up to 28°C)	suitable (up to 28°C)
Behaviour to fire EN 13501-1	Bfl-s1	Bfl-s1
Resistance to thermal conductivity ISO 8302	0.02 m ² K/W	0.02 m ² K/W
Impact sound improvement ISO 10140	6 db	6 db
Colour fastness EN 20105-B02/2	> 6	> 6
Electrostatic characteristics EN 1081	> 10 ¹⁰	> 10 ¹⁰
Chemical resistance EN 423	conforms*	conforms*
Slip resistance	R9	R9
Maintenance/Cleaning recommendation	CC-Dr. Schutz	CC-Dr. Schutz

*Vis-à-vis the short-term effects of normal, domestic agents.

Please also note the installation and cleaning and care instructions.

(Date: 01/10/2015)



